### (19) World Intellectual Property Organization International Bureau



# 

#### (43) International Publication Date 10 May 2001 (10.05.2001)

# **PCT**

## (10) International Publication Number WO 01/32398 A1

(51) International Patent Classification7: A61M 25/00

B29C 47/92,

- (74) Agents: CROMPTON, David, M. et al.; Crompton, Sea-
- (21) International Application Number: PCT/US00/41223
- (22) International Filing Date: 18 October 2000 (18.10.2000)
- (25) Filing Language:

English

(26) Publication Language:

English

US

(30) Priority Data: 09/430,327

29 October 1999 (29.10.1999)

- (71) Applicant: SCIMED LIFE SYSTEMS, INC. [US/US]; One SciMed Place, Maple Grove, MN 55311-1566 (US).
- (72) Inventors: CENTELL, Donald, L.; 1549 Poppybank Court, Pleasanton, CA 94566 (US). ALPERT, Lawrence, C.; 39661 Royal Palm Drive, Fremont, CA 94538 (US).


- ger & Tufte, LLC, Suite 895, 331 Second Avenue South, Minneapolis, MN 55401-2246 (US).
- (81) Designated States (national): CA, JP.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

#### Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR EXTRUDING CATHETER TUBING



(57) Abstract: Systems and methods for fabricating medical catheters are disclosed. A system in accordance with the present invention includes a first melt pump in fluid communication with an extrusion head, a second melt pump in fluid communication with the extrusion head, a puller arranged to receive extrudate emerging from the extrusion head, a first drive coupled to the first melt pump, a second drive coupled to the second melt pump, a third drive coupled to the puller, an encoder coupled to the third drive and being adapted to measure the length of extrudate passing through the puller, and a computer coupled to the first drive, the second drive, the third drive, and the encoder.

